



TIMOTHY OULTON

ASSEMBLY INSTRUCTION

REX MIR TALL 220X123CM

PARTS ENCLOSED

ITEMS	DIAGRAM	DESCRIPTION	QTY.
(A)		Body	1
(A1)		Bolt Nuts	36
(A2)		Bolt Bolts	36
(A3)		Glass Rods	
(A4)		Corner Connectors	2
(B)		Mounting Screws (Not included)	4
(C1)		Spare Glass Dods	5
(C2)		Spare Glass Dods	5
(D)		Bulbs+Spare	24+7

IMPORTANT SAFETY INSTRUCTIONS:

1. Use an authorized and certified electrician for consultation and installation.
2. This fixture has been rated for twenty-four (24) 25watt maximum E12 bulbs.
3. To avoid the risk of fire, do not exceed the recommended wattage.
4. The manufacturer and distributor accept no liability for incorrect installation.
5. For indoor use only.
6. Keep away from children.

WARNINGS:

1. Turn-off electricity supply at main circuit panel before installing. Do not connect electricity supply until your lamp is fully assembled and installed.
2. All wires are connected. Do not remove the lamp from its packaging by pulling on the power cord, as a bad connection may result.
3. To reduce the risk of fire, electrical shock, or personal injury, always turn off the lamp and allow it to cool prior to replacing light bulb. Do not touch bulb when fixture is turned on or look directly at light bulb. Keep flammable materials away from light bulb.
4. Deviation from instructions may result in a risk of fire or electric shock.

PRODUCT DESCRIPTION:

General material: Glass & Iron
 Length: 220.0cm (87.0in)
 Width: 123.00cm (48.4in)
 Height: 15.5cm (6.1in)
 Weight: 136.0kg (300.1lbs)

ASSEMBLY INSTRUCTIONS:

1. Carefully remove all parts from the box and remove all plastic covering.
2. Lean the mirror body (A) on the wall as shown in the diagram.
3. Attach the corner connector from the mirror body to the wall with mounting screws (B), ensure the mirror body securely fixed to the wall.
4. Fasten the bulbs (D) to the lampholders.
4. Insert plug into socket and test floor lamp fixture.

REPLACE THE GLASS:

Loosen the bolt nuts (A1) and bolts (A2), detach the metal plate and metal ring from body (A). Loosen the bolts at both ends of the glass rods (A3) and remove the glass rods. Attach the glass rods (C1 or C2) to the body with fasten the bolts in both ends of the glass rod. Place the metal plate and metal ring to body (A) and fasten the bolts (A2).

CARE INSTRUCTIONS:

1. Make sure that the power is turned off and bulb has cooled before handling.
2. Wipe clean with a dry cloth. Do not use corrosive cleaners.
3. The cable/cord of this floor lamp cannot be replaced: if the cable is damaged, do not use the lamp.

ENVIRONMENT:

Special waste handing may be required. Please contact your local authorities for more information.

